



Model: WR1200

AC1200

Dual Band Smart Wi-Fi Router





Features

- AC1200 Dual Band Wi-Fi Router
- 2.4 GHz 300Mbps + 5 GHz 867Mbps Wi-Fi Speeds
- 5dBi High Gain Antennas for large home coverage
- Built-in Firewall protect your home network
- Guest network protect your privacy
- Compatible with IPv6
- Easy wireless security encryption at a push of WPS button

Specifications

Product Name	AC1200 Dual Band Smart Wi-Fi Router
Product Model	WR1200
Standard	2.4GHz:IEEE802.11n、 IEEE802.11g、 IEEE 802.11b
	5.0GHz:802.11ac、 IEEE 802.11n、 IEEE 802.11a
	IEEE802.3、 IEEE802.3u、 IEEE802.3ab
Interface	LAN 4 *10/100/ Auto MDI/MDIX RJ45 port;
	WAN 1* 10/100/ Auto MDI/MDIX RJ45 port
Frequency Range	2.4GHz/5GHz
Wireless Speed	2.4G: 300Mbps, 5G: 867Mbps
Transmit Power	CE: <20dBm(2.4 GHz), <23dBm(5.15 GHz~5.25 GHz)
	FCC:<30dBm(2.4 GHz & 5.15 GHz~5.825 GHz)
Flash	64Mbit (8MB)
DDR	512Mbit (64MB)
Power	12V/ 1A
Spread Spectrum	DSSS
Modulation	BPSK, QPSK, CCK and OFDM (BPSK/QPSK/16-QAM/ 64-QAM)
Antenna	4x5dBi Fixed Antenna
Data Security	64/128-bits WPA-PSK/WPA2-PSK, WPA/WPA2
VPN Client	PPTP/L2TP
CWMP Protocol	TR069 / TR098 / TR111 / TR181
ACS Server Compatibility	GenieACS, Open ACS
Working Mode	Wi-Fi Router/ Wireless Access Point/Wi-Fi Extender/ WISP



Specifications

Management	Access Control, Local Management, Remote Management, Wake on LAN
TTL	Extend/Spoof/Custom
DNS	Default/Custom
Internet Protocols	IPv4 / IPv6
IPv6	Relay
	Dynamic(SLAAC/DHCPv6)
	Static (Fixed IP)
	Passthrough
	MAP-E (Dual-stack)
	DS-Lite (Dual-stack)
Environment	Operating Temperature: 0°C~40°C (32°F~104°F)
	Operating Humidity: 10%~90%RH (non-condensing)